





SPY 90 92745 ADM

19883 9230 W

AVAILABLE IN  
**SCHWARZ** 19883 9230 B  
**WEISS** 19883 9230 W



 [View on website](#)



General info

|                    |                                                                                            |
|--------------------|--------------------------------------------------------------------------------------------|
| LOCATION           | innenbereich                                                                               |
| INSTALLATION       | Schiene Schienenmontiert                                                                   |
| INGRESS PROTECTION | IP20                                                                                       |
| WEIGHT (KG)        | 1                                                                                          |
| ADJUSTABILITY      | 0° to 90° schwenkbar, 355° drehbar                                                         |
| INFORMATION        | REFLECTOR WFL-45°<br>3F POWER ADAPTER 1050mA-DC<br>Optional REFLECTORS 18° & 30° available |

Electrical info

|              |                    |
|--------------|--------------------|
| ELECTRICAL   | 220-240V / 50-60Hz |
| CLASS        | II                 |
| POWER SUPPLY | YES                |
| DIM TYPE     | nicht dimmbar      |
| ENERGY CLASS | D                  |
| CERTIFICATES | CB, ENEC, RCM      |

Lightsource info

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED array 36W / CRI>90 (R9: 60) / 2700K / 4393lm |
| TM-30 VALUES                | rf: 89 / Rg: 100                                 |
| SDCM                        | SDCM1                                            |
| RISKGROUP                   | RG1                                              |
| LM80                        | L90B10 > 50000                                   |
| BEAMANGLE                   | 45°                                              |
| LED TECHNICS (LIGHT SOURCE) | 4393lm // 36W // 122lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 3107lm // 41,4W // 75lm/W                        |

Requirements

SPY 90 TUBE  
TRACK 3F DIM


Accessories

HONEYCOMB 75  
SPREAD LENS 75  
LINEAR SPREAD LENS 75  
SOFTENING LENS 75  
GLASS SBL 75

For detailed installation instructions, please consult the manual : [19883\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Licht veredelndes Zubehör




<sup>13</sup> **19810 0110 B** HONEYCOMB 75 SINGLE USE B

☐



<sup>14</sup> **19810 0120 B** HONEYCOMB 75 DOUBLE USE B

☐




<sup>13</sup> **19810 0130** GLASS SBL 75

☐




<sup>13</sup> **19810 0140** LINEAR SPREAD LENS 75

☐



<sup>13</sup> **19810 0150** SOFTENING LENS 75

☐



<sup>13</sup> **19810 0160** SPREAD LENS 75

☐

#### Beenden Sie Ihr Produkt



<sup>28</sup> **19810 0170 B** SPY 90 TUBE B

☐

# DELTALIGHT

## SPY 90 92745 ADM

19883 9230 W

|                       |                 |                          |
|-----------------------|-----------------|--------------------------|
| <b>19810 0170 CR</b>  | SPY 90 TUBE CR  | <input type="checkbox"/> |
| <b>19810 0170 DC</b>  | SPY 90 TUBE DC  | <input type="checkbox"/> |
| <b>19810 0170 FBR</b> | SPY 90 TUBE FBR | <input type="checkbox"/> |
| <b>19810 0170 FG</b>  | SPY 90 TUBE FG  | <input type="checkbox"/> |
| <b>19810 0170 GC</b>  | SPY 90 TUBE GC  | <input type="checkbox"/> |
| <b>19810 0170 PB</b>  | SPY 90 TUBE PB  | <input type="checkbox"/> |
| <b>19810 0170 W</b>   | SPY 90 TUBE W   | <input type="checkbox"/> |

### Austauschbarer Reflektor / Linse

|                                                                                    |                                        |                          |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|  | <b>19810 0200</b> SPY 90 REFLECTOR 18° | <input type="checkbox"/> |
|  | <b>19810 0210</b> SPY 90 REFLECTOR 30° | <input type="checkbox"/> |
|  | <b>19810 0220</b> SPY 90 REFLECTOR 45° | <input type="checkbox"/> |

## COMPATIBLE TRACKS

| TRACK 3F DIM H    |                    |        |        | Available Colours                                      |
|-------------------|--------------------|--------|--------|--------------------------------------------------------|
| <b>200 14 410</b> | TRACK 3F DIM H 1m  | 1000 m | 1.6 kg | <input checked="" type="radio"/> <input type="radio"/> |
| <b>200 14 420</b> | TRACK 3F DIM H 2m  | 2000 m | 3.2 kg | <input checked="" type="radio"/> <input type="radio"/> |
| <b>200 14 430</b> | TRACK 3F DIM H 3m  | 3000 m | 4.8 kg | <input checked="" type="radio"/> <input type="radio"/> |
| TRACK 3F DIM IN   |                    |        |        | Available Colours                                      |
| <b>200 13 410</b> | TRACK 3F DIM IN 1m | 1000 m | 1.2 kg | <input checked="" type="radio"/> <input type="radio"/> |

# DELTALIGHT

## SPY 90 92745 ADM

19883 9230 W

|                                      |        |        |                                                                                                                                                                                                                                                             |
|--------------------------------------|--------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>200 13 420</b> TRACK 3F DIM IN 2m | 2000 m | 2.4 kg |                                                                                       |
| <b>200 13 430</b> TRACK 3F DIM IN 3m | 3000 m | 3.5 kg |                                                                                       |
| <b>TRACK 3F DIM ON</b>               |        |        | <b>Available Colours</b>                                                                                                                                                                                                                                    |
| <b>200 12 410</b> TRACK 3F DIM ON 1m | 1000 m | 1.1 kg |    |
| <b>200 12 420</b> TRACK 3F DIM ON 2m | 2000 m | 2.1 kg |    |
| <b>200 12 430</b> TRACK 3F DIM ON 3m | 3000 m | 3.1 kg |    |

Notes: