





COMPO S WALLWASH TW 940

9 15718 9000 C

AVAILABLE IN
CHROMED 9 15718 9000 C
WHITE 9 15718 9000 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.128
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,3W / CRI>90 / 1800K-4000K / 604lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	604lm // 5,3W // 113lm/W
LED TECHNICS (LUMINAIRE)	230lm // 6,1W // 38lm/W

Requirements

LED POWER SUPPLY 150 mA - DC

For detailed installation instructions, please consult the manual : [9_15718_XXX0_HAND.pdf](#)

COMPO S WALLWASH TW 940

9 15718 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 5700 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 150mA	1

Mounting kits		
	15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
Cutout dimension (mm): 55		
	15710 0010 W MOUNTING KIT COMPO S TRIM W	☐
	15710 0040 MOUNTING KIT COMPO S TRIMLESS	☐
Cutout dimension (mm): 55		

Notes: