DELTALIGHT



BOXY L HE 94020 DIM8

REFERENCE 10747 9428 W-W

AVAILABLE IN
BLACK-BLACK 10747 9428 B-B
BLACK-FLEMISH BRONZE 10747 9428 B-FBR
BLACK-FLEMISH GOLD 10747 9428 B-FG
WHITE-WHITE 10747 9428 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-20° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 60) / 4000K / 975lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	975lm // 6W // 163lm/W
LED TECHNICS (LUMINAIRE)	855lm // 7W // 124lm/W

Remarks

High Efficacy : > 100lm/W

For detailed installation instructions, please consult the manual : **10747_XXX8_HAND.pdf**

DELTALIGHT

BOXY L HE 94020 DIM8

10747 9428 W-W

Notes: