



TWEETER M ON 2 92750 DIM8



REFERENCE

418 51 812 923 ED8 B-C

AVAILABLE IN

NOIR-CHROME 418 51 812 923 ED8 B-C

BLANC-BLANC 418 51 812 923 ED8 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique,Mur Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	2 x REFLECTOR WFL-50° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm)
RVALUES	Rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2082lm // 17,2W // 121lm/W
LED TECHNICS (LUMINAIRE)	1596lm // 19,8W // 81lm/W


For detailed installation instructions, please consult the manual : [418_51_812_XXX_HAND.pdf](#)

TWEETER M ON 2 92750 DIM8

418 51 812 923 ED8 B-C

FINISH YOUR SPECIFICATION

Equipements de contrôle divers



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 40

Notes: