





## COMPO L WALLWASH 927

9 15739 9200 C

AVAILABLE IN

**CHROMED** 9 15739 9200 C

**WHITE** 9 15739 9200 W



[View on website](#)



### General info

|                                           |                                     |
|-------------------------------------------|-------------------------------------|
| <b>LOCATION</b>                           | indoor                              |
| <b>INSTALLATION</b>                       | Ceiling Recessed                    |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 135                         |
| <b>RECESSED DEPTH (MM)</b>                | 130                                 |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | max.25                              |
| <b>INGRESS PROTECTION</b>                 | IP20                                |
| <b>WEIGHT (KG)</b>                        | 0.46                                |
| <b>ADJUSTABILITY</b>                      | 0° to 30° swiveling, 355° rotatable |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | F                         |

### Lightsource info

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                |
| <b>LIGHTSOURCE</b>                 | LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                   |
| <b>SDCM</b>                        | SDCM1                                              |
| <b>RISKGROUP</b>                   | RG1                                                |
| <b>LM80</b>                        | L90B10 > 50000                                     |
| <b>BEAMANGLE</b>                   | NA                                                 |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 2009lm // 17,2W // 117lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 880lm // 19,8W // 44lm/W                           |

### Requirements

LED POWER SUPPLY 500 mA - DC

For detailed installation instructions, please consult the manual : [9\\_15739\\_XXX0\\_HAND.pdf](#)

## COMPO L WALLWASH 927

9 15739 9200 C

### CEILING COMPATIBILITY

| Ceiling Type                                                                                           | Mounting Kit                                                                                                                 |          |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------|
|  <b>System ceiling</b> |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                                        |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  <b>Plasterboard</b>   |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                                        |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  <b>Wood</b>           |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                                        |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |

### FINISH YOUR SPECIFICATION

#### LED Power supply

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

**15710 3600** LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA

1

**15710 4200** LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA

1

**15710 4700** LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA

1

**15710 5400** LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA

1

Dimtype: DALI

#### Mounting kits



**15710 0030 B** MOUNTING KIT COMPO L TRIM B

Cutout dimension (mm): 92

**15710 0030 W** MOUNTING KIT COMPO L TRIM W



**15710 0060** MOUNTING KIT COMPO L TRIMLESS

Cutout dimension (mm): 92

# DELTALIGHT

## COMPO L WALLWASH 927

9 15739 9200 C

Notes: