



## M - HEDRA 39 C 93045 DIM5

22539 9335 B



AVAILABLE IN

**BLACK** 22539 9335 B

**BLACK BRONZE** 22539 9335 BBR

**GOLD COLOURED** 22539 9335 GC

**WHITE** 22539 9335 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC INCL.1 x CABLE 2 x 0.75mm <sup>2</sup>

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	45°
<b>LED TECHNICS (LIGHT SOURCE)</b>	787lm // 5,8W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	530lm // 6,7W // 79lm/W

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [22539\\_XXX5\\_HAND.pdf](#)

# DELTALIGHT

## M - HEDRA 39 C 93045 DIM5

22539 9335 B

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

12


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

29

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

12

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

24

Dimtype: non-dimmable

Cutout dimension (mm): 40

### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26H + SBL

#### Available Colours



**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



**30411 9305** SHIFTLINE M26H + SBL 2m DIM5




**30412 9205** SHIFTLINE M26H + SBL 3m DIM5




# DELTALIGHT

## M - HEDRA 39 C 93045 DIM5


22539 9335 B



**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5




**30413 9305** SHIFTLINE M26H + SBL 4m DIM5




### SHIFTLINE M26H profile


### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m




**23359 0030** SLM26H - PROFILE 3m




### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

### Available Colours



**23358 0000** SLM26L - PROFILE




**23358 0010** SLM26L - PROFILE 1m




# DELTALIGHT

## M - HEDRA 39 C 93045 DIM5

22539 9335 B



**23358 0020** SLM26L - PROFILE 2m



**23358 0030** SLM26L - PROFILE 3m



### SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B




# DELTALIGHT

## M - HEDRA 39 C 93045 DIM5


22539 9335 B

### SPLITLINE M52 profile


### Available Colours




**420 52 10 00** SPM52 - PROFILE 1m



**420 52 20 00** SPM52 - PROFILE 2m



**420 52 30 00** SPM52 - PROFILE 3m



**24413 0000** SPM52 - PROFILE



Notes: