



EXCLUSIVELY AVAILABLE IN INDIA

COMPO S IP44 HP 94020

9 15747 9420 B



AVAILABLE IN

SCHWARZ 9 15747 9420 B

CHROM 9 15747 9420 C

DUNKLES CHROM 9 15747 9420 DC

WEISS 9 15747 9420 W



[View on website](#)



General info

LOCATION	innen-aussenbereich
INSTALLATION	Decke Einbau
CUTOUT SHAPE/SIZE (MM)	rund - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.178
ADJUSTABILITY	0° to 30° schwenkbar, 355° drehbar

Electrical info

CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9,3W / CRI>90 / 4000K / 973lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	973lm // 9,3W // 104lm/W
LED TECHNICS (LUMINAIRE)	772lm // 10,7W // 72lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15747_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO S IP44 HP 94020

9 15747 9420 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Netzteil

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3100 LED POWER SUPPLY 18W NO DIM 1400mA 1->4

15710 3400 LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA 1->2

15710 3900 LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA 1

15710 4600 LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA 1

15710 5000 LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA 1->13

Dimtype: DALI

15710 5400 LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA 1->2

Dimtype: DALI

Mounting Kit



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W

COMPO S IP44 HP 94020

9 15747 9420 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Licht veredelndes Zubehör

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: