



## M26L - SPY 391 L 92720 MDL

23284 9220 W

AVAILABLE IN



**BLACK** 23284 9220 B

**FLEMISH BRONZE** 23284 9220 FBR

**FLEMISH GOLD** 23284 9220 FG

**GOLD COLOURED** 23284 9220 GC

**WHITE** 23284 9220 W



[View on website](#)



### General info

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>LOCATION</b>           | indoor                                          |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted  |
| <b>INGRESS PROTECTION</b> | IP20                                            |
| <b>WEIGHT (KG)</b>        | 0.4                                             |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 360° rotatable             |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>EXCLLED POWER SUPPLY 48V-DC |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC, EPD                      |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                  |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 20°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1041lm // 8,6W // 121lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 652lm // 9,9W // 66lm/W                           |

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

SPY 39 L TUBE  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23284\\_XXX0\\_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = wireless dimmable


19

SMART 48

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

Dimtype: 1-10V or DALI or push button

19



**300 90 012** SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable


19

LED power supplies

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN




Dimtype: non-dimmable

10


# DELTALIGHT

## M26L - SPY 391 L 92720 MDL



23284 9220 W

|                                                                                  |                                                         |    |                          |
|----------------------------------------------------------------------------------|---------------------------------------------------------|----|--------------------------|
|  | <b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN | 24 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
|  | <b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W        | 10 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |
|  | <b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W        | 20 | <input type="checkbox"/> |
| Dimtype: non-dimmable                                                            |                                                         |    |                          |
| Cutout dimension (mm): 40                                                        |                                                         |    |                          |

### Finish your product

|                                                                                   |                                     |                          |
|-----------------------------------------------------------------------------------|-------------------------------------|--------------------------|
|  | <b>24144 0020 B</b> SPY 39 L TUBE B | <input type="checkbox"/> |
| <b>24144 0020 FBR</b> SPY 39 L TUBE FBR                                           |                                     | <input type="checkbox"/> |
| <b>24144 0020 FG</b> SPY 39 L TUBE FG                                             |                                     | <input type="checkbox"/> |
| <b>24144 0020 GC</b> SPY 39 L TUBE GC                                             |                                     | <input type="checkbox"/> |
| <b>24144 0020 W</b> SPY 39 L TUBE W                                               |                                     | <input type="checkbox"/> |


## COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                    | Available Colours                                                                                                           |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
|  | <b>23358 0000</b> SLM26L - PROFILE     |
|  | <b>23358 0010</b> SLM26L - PROFILE 1m  |


# DELTALIGHT

## M26L - SPY 391 L 92720 MDL

23284 9220 W



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m




### SHIFTLINE M35R profile


### Available Colours




**23375 0000** SLM35R - PROFILE



**23375 0010** SLM35R - PROFILE 1m



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: