DELTALIGHT



MULTINOVA 55 SOFT 930 DIM5

REFERENCE 28016 9005 W

AVAILABLE IN
BLACK 28016 9005 B
GOLD COLOURED 28016 9005 GC
WHITE 28016 9005 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 32,3W / CRI>90 (R9: 50) / 3000K-1800K / 4567lm
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4567lm // 32,3W // 141lm/W
LED TECHNICS (LUMINAIRE)	3681lm // 37W // 99lm/W

Options

MULTINOVA 55 SUSPENSION SET
MULTINOVA ROD SUSPENSION
MULTINOVA 55 RECESSED KIT

For detailed installation instructions, please consult the manual : **28016_XXX5_HAND.pdf**

DELTALIGHT

MULTINOVA 55 SOFT 930 DIM5

28016 9005 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required
 **Plasterboard**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required
 **Stucanet**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required
 **Concrete + plaster**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required
 **Lintel + plaster**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required
 **Hollow-core slab + plaster**	28010 0050 - MULTINOVA 55 RECESSED KIT	Required

FINISH YOUR SPECIFICATION

Recessed kits



28010 0050 MULTINOVA 55 RECESSED KIT ☐

Cutout dimension (mm): 610

Suspension parts



27910 0010 B MULTINOVA 55 SUSPENSION SET 5x0,75 3m B ☐

27910 0010 W MULTINOVA 55 SUSPENSION SET 5x0,75 3m W ☐



27910 0030 B MULTINOVA 55 ROD SUSPENSION 0,4m B ☐

27910 0030 W MULTINOVA 55 ROD SUSPENSION 0,4m W ☐

DELTALIGHT

MULTINOVA 55 SOFT 930 DIM5

28016 9005 W



27910 0040 B MULTINOVA 55 ROD SUSPENSION 0,8m B ☐

27910 0040 W MULTINOVA 55 ROD SUSPENSION 0,8m W ☐

Notes: