

EXCLUSIVELY AVAILABLE IN INDIA



COMPO L WALLWASH 940

9 15739 9400 C

AVAILABLE IN

CHROME 9 15739 9400 C

BLANC 9 15739 9400 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.46
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,2W / CRI>90 (R9: 79) / 4000K / 2222lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	2222lm // 17,2W // 130lm/W
LED TECHNICS (LUMINAIRE)	973lm // 19,8W // 49lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

For detailed installation instructions, please consult the manual : [9_15739_XXX0_HAND.pdf](#)

COMPO L WALLWASH 940

9 15739 9400 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
15710 3600	LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA	1 ☐
15710 4200	LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA	1 ☐
15710 4700	LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA	1 ☐
15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1 ☐
Dimtype: DALI		

kit de montage	
	15710 0030 B MOUNTING KIT COMPO L TRIM B ☐
Cutout dimension (mm): 92	
	15710 0030 W MOUNTING KIT COMPO L TRIM W ☐
	15710 0060 MOUNTING KIT COMPO L TRIMLESS ☐
Cutout dimension (mm): 92	

DELTALIGHT

COMPO L WALLWASH 940

9 15739 9400 C

Notes: