

LUNELLE 52 ON 2 48V 92730 DIM5

32815 9225 BRA-B

AVAILABLE IN

BRUSHED ALU-BLACK 32815 9225 BRA-B



BRUSHED ANTHRACITE-BLACK 32815 9225 BRAT-B

BRUSHED BROWN BRONZE BLACK 32815 9225 BRBB-B

BRUSHED COPPER-BLACK 32815 9225 BRCU-B

BRUSHED GOLD-BLACK 32815 9225 BRG-B

BRUSHED OLD BRONZE-BLACK 32815 9225 BROB-B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V-DC

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : [32815_XXX5_HAND.pdf](#)


DELTALIGHT

LUNELLE 52 ON 2 48V 92730 DIM5

32815 9225 BRA-B

FINISH YOUR SPECIFICATION

LED power supplies



21032 0390 LED POWER SUPPLY 48V-DC / 90W

Dimtype: non-dimmable

Cutout dimension (mm): 75



21032 0600 LED POWER SUPPLY 48V-DC / 35W

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



32810 0010 DC VISOR 52 DC

Notes: