





M26L - JUM-OH! 2R 93030 DIM5

29412 9325 B

AVAILABLE IN
BLACK 29412 9325 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4W / CRI>90 (R9: 60) / 3000K / 481lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	481lm // 4W // 120lm/W
LED TECHNICS (LUMINAIRE)	398lm // 4,6W // 86lm/W
Requirements	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [29412_XXX5_HAND.pdf](#)

M26L - JUM-OH! 2R 93030 DIM5

29412 9325 B

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100	LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	21
63114125 300 89 48 240	LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	52
1729830 21012 0230	LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	21
2239230 21012 0240	LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	43


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
3226 23358 0000	SLM26L - PROFILE
3226 23358 0010	SLM26L - PROFILE 1m
3226 23358 0020	SLM26L - PROFILE 2m

DELTALIGHT

M26L - JUM-OH! 2R 93030 DIM5

29412 9325 B




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours




23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m



Notes: