





D-LINER 19 SBL LOC1 1220 940 RD
32039 9400 B

AVAILABLE IN
BLACK 32039 9400 B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 780mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green
Electrical info	
CLASS	III
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 30W / CRI>90 (R9: 59) / 4000K / 3120lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3120lm // 30W // lm/W
LED TECHNICS (LUMINAIRE)	2340lm // 34,5W // 68lm/W
Requirements	
LED POWER SUPPLY SET LOC PARALLEL	
Options	
CONNECTING CABLE LOC PARALLEL	

For detailed installation instructions, please consult the manual : [32039_XXX0_HAND.pdf](#)

D-LINER 19 SBL LOC1 1220 940 RD


32039 9400 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5	1
Dimtype: DALI		

Current supply

	32010 1200 T CONNECTOR LOC PARALLEL	
	32010 1310 CONNECTING CABLE LOC PARALLEL 1m	
	32010 1320 CONNECTING CABLE LOC PARALLEL 2m	
	32010 1330 CONNECTING CABLE LOC PARALLEL 3m	

DELTALIGHT

D-LINER 19 SBL LOC1 1220 940 RD

32039 9400 B



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

☐

32010 1350 CONNECTING CABLE LOC PARALLEL 5m

☐


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




32010 0125 LED POWER SUPPLY SET LOC PARALLEL 780mA / 35W DIM5

1

☐

Dimtype: DALI




32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5

2->2

☐

Dimtype: DALI



32010 0455 LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5

3->3

☐

Dimtype: DALI

Notes: