MULTINOVA 30 & 55



Listing
ETL certified to US and Canadian safety standards.
Warranty
5-year limited warranty.

As a disc of light, Nova refers to the Supernova range, as both families share similarities in looks and ways of installation. Offered as a down and down-up version and a limited height of only 2"-3/4, Multinova comes in our standard black or white and can also be finished in the warmer Gold Colored. To top it off – next to a opal sandblasted or prismatic optic – one can opt for a smoked sheet at the front for a more decorative touch. When turned on the disc is fully lit, when turned off a deep dark arises, ideal in combination with a Gold Colored Multinova.

Specification	Multinova Adjustable Pivot	Multinova Adjustable Suspended	Multinova Fixed		
Adjustability:	Adjustable 0-45° / 360°	Adjustable 0-90° / 355°	Fixed		
Rating:	IP20				

Performance	Static CCT (Down / Up)	Soft Dim		
LED Maintenance:	L80>60,000h	L80>60,000h		
McAdam Step:	3	3		
CRI:	90	90		
*R03 Down SP:	13.2W	13.2W		
*R03 Down-Up SP:	15W / 4.5W			
*R05 Down SP:	34.4W	32.3W		
*R05 Down-Up SP:	34.4W / 5.1W			

Delivered Lumens	3000K (Down)	3000K (Down/Up)	2700-1800K (Down)	
R03 Opal:	1423Lm	1423Lm/565Lm	1446Lm	
R03 Prism:	1256Lm	1256Lm/565Lm		
R03 Smoke:	865Lm	865Lm/565Lm		
R05 Opal:	3842Lm	3842Lm/668Lm	3681Lm	
R05 Prism:	3466Lm	3466Lm/668Lm		
R05 Smoke:	2303Lm	2303Lm/668Lm		

Ordering ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNVR05A-SR4XD1-120INC-SPDN30-GC-O

Luminaire	Shape	Size	Function	Style	Installation	Hardware Finish ⁽⁴⁾	Controls	Application ⁽⁴⁾	Downlight*	Uplight*	ССТ	Finish	Lens	
MNV MULTINOVA Round		03(1) 300mm 11 ¹³ / ₁₆ " 05 550mm 21 ²¹ / ₃₂ "		V Pivot Arm	MK Mud kit into drywall over 4"j-box	X No hardware Finish	D14-UNV 0-10V dim 120- 277V / FE ELV	120- Integral Power Supply	SP Standard Power	DN Downlight only, no uplight	30 3000K	B Black	O Opal	
				PR Round coverplate for 4* j-box		B Black W			DU (2) Downlight with uplight added	SD(3) 3000- 1800K	GC(5) Gold Colored	P(2,3) Prismatic		
				S(1) Suspended	R3(1) Rigid stem 702mm / 27°/ ₈ " Includes coverplate for 4" j-box R4(1) Rigid stem 1102mm / 43³/ ₈ " Includes coverplate for 4" j-box	X Stem finish coordinates with luminaire finish selected						W White	S(2) Smoke	
			F Fixed	PC Suspended	PR Round coverplate for 4" j-box 10" field-cuttable cables R1(1) Rigid stem 400mm / 15 ⁵ / ₄ " Includes coverplate for 4" j-box R2(1) Rigid stem 800mm / 311/ ₂ " Includes coverplate for 4" j-box	B Black W White	D1-120 0-10V dim 120V D5-120 Dali dim 120V							
				R(3) Recessed	K Mud in edge-finishing kit	X No hardware finish								
				S(3) Surface Mount	F Install onto 4" junction box									





⁴ Applies to PR/PS (coverplate) & R1/R2 (rigid stem). ⁵ Finish GC not offered with Lens Option P.







Related Products

Multinova 255/355, Supernova XS, Supernova XS ADM (track), Supernova

Finish Options

LENS









MULTINOVA R03 Adjustable Pivot












MULTINOVA R03 Fixed Down










MULTINOVA R03 Fixed Down-Up












MULTINOVA R05 Adjustable Pivot














Finish Options (cont'd)

MULTINOVA R05 Adjustable Suspended












MULTINOVA R05 Fixed Down












MULTINOVA R05 Fixed Down-Up











Installation Options

R03 PCPR



MULTINOVA 30 SUSPENSION SET (BLACK or WHITE)

Included for R03 Style PC Installation PR

Requires 4" junction box

R05 PCPR



MULTINOVA 55 SUSPENSION SET (BLACK or WHITE)

Included for R05 Style PC Installation PR

R05 RK



COVERPLATE R 212 (BLACK or WHITE)

Included for R05 Style PC Installation PR

Requires 4" junction box

R05 PCR1



MULTINOVA 55 S ROD SUSPENSION 16 (BLACK or WHITE)

Only available for Size 05

Requires 4" junction box

R05 PCR2



MULTINOVA 55 S ROD SUSPENSION 31 (BLACK or WHITE)

Only available for Size 05


Requires 4" junction box

R03 RK




RECESSED KIT Included for R03 Style R

MULTINOVA 30



MUI TINOVA 55 RECESSED KIT Included for R05 Style R

R03 VMK



MUD KIT 2

Only available for Style V

Requires 4" junction box



R03 VPR

COVERPLATE R 106 (BLACK or WHITE)

Only available for Style V


Requires 4" junction box










Photometric Data









Driver Options

D1

· Dimming Control 0-10V · Dimming Range 10-100% • Dim to off no • Power Factor @ Full Load >0.97 Efficiency @ Full Load

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX

D5

· Dimming Control Dali 1-100% · Dimming Range · Dim to off yes • Power Factor @ Full Load >0.9 Efficiency @ Full Load ≥85 THD @ Full Load <20%

D14 (With Style V only)

· Dimming Control Phase Control or -10V 1-100% · Dimming Range · Dim to off yes • Power Factor @ Full Load >0.9 Efficiency @ Full Load ≥90 THD @ Full Load <20%

Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- · Leviton DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- · Leviton IP710-DLZ
- Leviton DVTV-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.