
M-SPY 27, 39, FOCUS, & FRAMER



Spy is the most extensive spotlight family: different installation methods, multiple light refining accessories to be added, mid- and high-power LEDs in static CCTs as well as Soft Dim and Tunable White in the larger sizes. The petite Spy spotlights are excellent accent and task lighting. Incorporating Spy into our Magnetic systems gives the ultimate flexibility in layout and adaptable over time, as modules can easily be relocated within the system

| Specification | |
|----------------|-------------------------|
| LED Aperture | 1" |
| Adjustability: | Adjustable 0-85° / 355° |
| Rating: | IP20 |

| Performance | Spy 27 Single/Double | Soft Dim | |
|------------------|-------------------------|---------------|-------------|
| LED Maintenance: | L90>5 | | |
| McAdam Step: | | 2 | |
| CRI: | 9 | | |
| *SP: | 7W / 2 x 7W | 10W / 2 x 10W | 7W / 2 x 7W |

| Delivered Lumens | | | 3000-1800K | | | | |
|--------------------|-------|-------|------------|-------|-------|-------|-------|
| **See page 6 for | MS | MD | FC | FR | WW | MD | WW |
| full details | | | | | | | |
| M-Spy 27 S Single: | | 480Lm | | | | | |
| M-Spy 27 L Single: | | 288Lm | | | | | |
| M-Spy 39 S Single: | 888Lm | 883Lm | 303Lm | | 431Lm | 505Lm | 341Lm |
| M-Spy 39 L Single: | 683Lm | 737Lm | | 825Lm | | | |

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering SEE NEXT PAGE FOR SIZE 39

Example: SPY27S1-SP35MDA-B-B-M20H-MDL

| Luminaire | Size | Length | Style | Power* | ССТ | Optic** | Function | Finish | Inner Finish | Application ³ | Controls |
|------------|---|----------------------------|------------------------------|-------------------------|---|--------------------------|------------------------|---|--|--|---|
| SPY SPY | 27 27mm / 1 ¹ / ₁₆ " Diameter | S Standard L Long | 1 Single Spot 21 Double Spot | SP Standard Power | 27 2700K 30 3000K 35 3500K | MD Medium Spot 30° | A Adjustable | B Black FBR¹ Flemish Bronze FG¹ Flemish Gold GC¹ Gold Colored W White | B Black BV ² Black Visor | M20H Shiftline M26H / Shiftline M26H + SBL ⁴ / Splitline M20 / Splitline M20 ST Profile ML Shiftline M26L Profile | MDL ⁴ 0-10V dim via Modulator D5 Dali dim WD ⁴ Wireless dim |

1 Only available with Finish Black or White.

3 Profile system hardware specified separately. 4 Shiftline M26H + SBL only available with Controls D5.

Related Products

M-Spy 52/66/Focus, M-Microspy C (pendant), M-Vizir/Hedra, Spy 27, Spy 39, Spy 52, Spy 66, Spy Focus, Spy S, Spy C (pendant), Superloop-Spy 52/66/Focus MDL





Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER


Example: SPY39S2-SPSDMDA-W-B-ML-WD

| Luminaire | Size | Length | Style | Power* | ССТ | Optic** | Function | Finish | Inner Finish ⁵ | Installation | Application ⁶ | Controls |
|-----------|---|------------------------|----------------------------------|-------------------------|---|--|------------------------|--|---|--|---|---|
| SPY : | 39 39mm / 1 ¹⁷ / ₃₂ " Diameter | S Standard | 1 Single Spot | SP Standard Power | 30 3000K 35 3500K SD ³ 3000- 1800K | MS Medium Narrow Spot 20° MD Medium Spot 40° WW4.5 Wallwash FC5 FOCUS Field Adjustable 15-45° | A Adjustable | B Black BRA Brushed Aluminum BRAT Brushed Anthracite BRCU Brushed Copper BRG Brushed Gold BROB Brushed Old Bronze FBR Flemish Bronze FG Gold Colored PB4 Piano Black W White | B ⁵ Black BV ^{1,3,5} Black Visor FBR ⁵ Flemish Bronze FG ⁵ Flemish Gold GC ⁵ Gold Colored W ⁵ White | RS Surface trim for rigid surface | M20H Shiftline M26H / Shiftline M26H + SBL ⁷ / Splitline M20 / Splitline M20 ST Profile ML Shiftline M26L Profile M52 ² Splitline M52 Profile | MDL ⁷ 0-10V dim via Modulator D ⁵ Dali dim WD ⁷ Wireless dim |
| | | | 2 ² Double Spot | | Double | SP Standard 2700K 30 Medium Narrow Spot 20° MD Medium Spot 40° Spo | A Adjustable | B Black W White | | | | |
| | | L ¹ Long | 1 Single Spot | SP Standard Power | 27 2700K 30 3000K 35 3500K | MS Medium Narrow Spot 20° MD Medium Spot 40° | A Adjustable | B Black FBR Flemish Bronze FG Flemish Gold GC Gold Colored W White | | | | |
| | | | | | | FR FRAMER Field- controlled beam shape (square, circle, or triangle) | A Adjustable | В | | | | |

1 Inner Finish BV only available with Length S.
2 Splitline M52 only available with Style 1.
3 Inner Finish BV not available with CCT SD.
4 Optic WW not available in Finish PB.
5 No Inner Finish needed for Optic FC or Wit, Skip field.
6 Profile system hardware specified separately.
7 Shiftline M26H+SBL only available with Controls DS.

Finish Options - Spy 27

SPY 27 S SINGLE









(shown in Splitline M20)









For application M20H

For application ML

SPY 27 S DOUBLE









For application M20H

For application ML

SPY 27 INNER FINISH - LENGTH S ONLY













SPY 27 L SINGLE WITH INNER FINISH

















3

SPY 27 L DOUBLE WITH INNER FINISH










For appliction M20H

For appliction ML

Finish Options - Spy 39

SPY 39 S SINGLE



For application M20H



For application ML



For application M52



(shown in Splitline M20)



ALUMINUM (shown in Shiftline M26L)



(shown in Shiftline M26L)



BRUSHED COPPER (shown in Shiftline M26L)



BRUSHED GOLD (shown in Shiftline M26L)



BRUSHED OLD BRONZE



FLEMISH BRONZE (shown in Splitline M20)



FLEMISH GOLD (shown in Splitline M20)



GOLD COLORED (shown in Splitline M20)




PIANO BLACK (shown in Shiftline M26L)



(shown in Splitline M20)

SPY 39 S DOUBLE



For application M20H For application ML



(shown in Splitline M20)

WHITE (shown in Splitline M20)

SPY 39 INNER FINISH - LENGTH S ONLY

















SPY 39 S SINGLE FOCUS



0-85°355°



For application M20H For application ML



BLACK (shown in Splitline M20)



BRUSHED ALUMINUM



BRUSHED ANTHRACITE



BRUSHED COPPER (shown in Shiftline M20)



BRUSHED GOLD (shown in Shiftline M20)

BRUSHED GOLD



BRUSHED OLD BRONZE (shown in Shiftline M26L)



FLEMISH BRONZE (shown in Splitline M20)




FLEMISH GOLD GOLD COLORED (shown in Splitline M20)




WHITE (shown in Splitline M20)

SPY 39 S SINGLE WALLWASH



0-85°355°



For application M20H For application ML



BLACK (shown in Splitline M20)



BRUSHED ALUMINUM



GOLD COLORED

WHITE

BRUSHED COPPER

(shown in Shiftline M20)

(shown in Splitline M20)



FLEMISH BRONZE



Finish Options - Spy 39

SPY 39 L SINGLE



SPY 39 INNER FINISH - LENGTH L ONLY














SPY 39 L SINGLE FRAMER









For application M20H

For application ML

Light Effects


SPY 39 L FRAMER CLIP













Photometric Data

| Delivered Lumens | 2700K | | | | | 3000K | | | | 3500K | | | | 3000-1800K | | | | |
|-------------------------|--------|--------|-------|-------|-------|--------|--------|-------|-------|-------|--------|--------|-------|------------|-------|--------|--------|-------|
| **Optic: | MS | MD | FC | FR | ww | MS | MD | FC | FR | ww | MS | MD | FC | FR | WW | MS | MD | ww |
| M-Spy 27 S Single: | | 459Lm | | | | | 480Lm | | | | | 498Lm | | | | | | |
| M-Spy 27 S Double: | | 919Lm | | | | | 960Lm | | | | | 995Lm | | | | | | |
| M-Spy 27 L Single: | | 276Lm | | | | | 288Lm | | | | | 299Lm | | | | | | |
| M-Spy 27 L Double: | | 551Lm | | | | | 576Lm | | | | | 598Lm | | | | | | |
| M-Spy 39 S Single: | 849Lm | 844Lm | 290Lm | | 413Lm | 888Lm | 883Lm | 303Lm | | 431Lm | 888Lm | 914Lm | 314Lm | | 447Lm | 508Lm | 505Lm | 341Lm |
| M-Spy 39 S Double: | 1697Lm | 1688Lm | | | | 1776Lm | 1766Lm | | | | 1776Lm | 1829Lm | | | | 1016Lm | 1010Lm | |
| M-Spy 39 L Single: | 652Lm | 705Lm | | 794Lm | | 683Lm | 737Lm | | 825Lm | | 683Lm | 764Lm | | 855Lm | | | | |




SPY 39 S


15° 45° MS 20° FC 15-45°



SPY 39 L



SPY 39 SOFT DIM



Soft Dim technology replicates the dimming behavior of a conventional lamp where the color temperature increases in warmth as it is dimmed. This is achieved through the use of specialty selected LEDs of different color temperatures and power types from premium chip manufacturers. Consistancy is ensured without complexity with the use of specific and precise LED selection. The LED's selected have color tolerances that are higher than 2 SDCM ensuring module-tomodule accuracy.

6

Installation Options

Deltalight's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

| Maximum Capacity per | Spy 27 | Spy 27 | Spy 39 | Spy 39 | Spy 39 Single |
|----------------------|--------|--------|--------|--------|---------------|
| Remote Power Supply | Single | Double | Single | Double | WW / Soft Dim |
| *SP: | 12 | 6 | 8 | 4 | 12 |

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:

Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)

Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)

Shiftline M26L (surface/suspended, low-height, stacking possible)

Splittine M20 (recessed, knife-edge, optional curved corner connectors)
Splittine M20 ST (recessed, small trim)

Splitline M52 (recessed, knife-edge)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.