



M52 - SPY 391 93020 MDL

REFERENCE

24430 9320 W

AVAILABLE IN



BLACK 24430 9320 B

FLEMISH BRONZE 24430 9320 FBR

FLEMISH GOLD 24430 9320 FG

GOLD COLOURED 24430 9320 GC

WHITE 24430 9320 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLEDLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [24430_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply		# of Fixtures
		Min current Max current
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>21032 0030</div><div>SMART 48 MODULATOR PLUG-IN WD</div></div></div>	19	<div></div>
<div>Dimtype: WDL = wireless dimmable</div>		
SMART 48		# of Fixtures
		Min current Max current
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>300 90 011</div><div>SMART 48 MODULATOR DIM9</div></div></div>	19	<div></div>
<div>Dimtype: 1-10V or DALI or push button</div>		
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>300 90 012</div><div>SMART 48 MODULATOR WD</div></div></div>	19	<div></div>
<div>Dimtype: WDL = wireless dimmable</div>		
LED power supplies		# of Fixtures
		Min current Max current
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div>		
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>300 89 48 100</div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div></div></div>	10	<div></div>
<div>Dimtype: non-dimmable</div>		

DELTALIGHT

M52 - SPY 391 93020 MDL

24430 9320 W




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

☐

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W


20

☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



24144 0030 B VISOR 39 B

☐

Finish your product



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FC SPY 39 TUBE FC

☐

24144 0010 GC SPY 39 TUBE GC

☐





24144 0010 W SPY 39 TUBE W

☐

24144 0070 SPY 39 TUBE SBL

☐

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile		Available Colours
	420 52 10 00 SPM52 - PROFILE 1m	
	420 52 20 00 SPM52 - PROFILE 2m	
	420 52 30 00 SPM52 - PROFILE 3m	
	24413 0000 SPM52 - PROFILE	

Notes: