



SPL14 - SPY 39 L 92720 MDL

27323 9220 B

AVAILABLE IN



BLACK 27323 9220 B

FLEMISH BRONZE 27323 9220 FBR

FLEMISH GOLD 27323 9220 FG

GOLD COLOURED 27323 9220 GC

WHITE 27323 9220 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCLLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	652lm // 9,9W // 66lm/W

Requirements

SPY 39 L TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27323_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SPL14 - SPY 39 L 92720 MDL



27323 9220 B

Finish your product

	24144 0020 B SPY 39 L TUBE B	☐
	24144 0020 FBR SPY 39 L TUBE FBR	☐
	24144 0020 FG SPY 39 L TUBE FG	☐
	24144 0020 GC SPY 39 L TUBE GC	☐
	24144 0020 W SPY 39 L TUBE W	☐

COMPATIBLE COMPOSABLES

D-LINER SHIFTLINE 19		Available Colours
	<u>29110 0010</u> D-LINER 19 SL PROFILE SET SAPP 2m	
	<u>29110 0030</u> D-LINER 19 SL PROFILE SET 30BD 2m	

SPLITLINE 14 profile		Available Colours
	27300 0020 SPL14 - PROFILE 2m	
	27300 0030 SPL14 - PROFILE 3m	

Notes:

DELTALIGHT

SPL14 - SPY 39 L 92720 MDL

27323 9220 B