



SPLITBOX 2 SPY 52 TW 93045

100072 9030 B

AVAILABLE IN
BLACK 100072 9030 B
WHITE 100072 9030 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 275 x 150
RECESSED DEPTH (MM)	180
THICKNESS OF MOUNTING SURFACE (MM)	max.12
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.8
INFORMATION	ADJUSTABLE 2 x REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 20° & 30° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2174lm // 18W // 121lm/W
LED TECHNICS (LUMINAIRE)	1391lm // 20,7W // 67lm/W

Requirements	
SPY 52 TUBE	
LED POWER SUPPLY 500mA-DC TW	

Accessories	
HONEYCOMB 42	
SPREAD LENS 42	
LINEAR SPREAD LENS 42	
SOFTENING LENS 42	
GLASS SBL 42	

DELTALIGHT

SPLITBOX 2 SPY 52 TW 93045

100072 9030 B

For detailed installation instructions, please consult the manual : [100072_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Dimtype: DALI


Cutout dimension (mm): 85

1


Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B



19810 0020 LINEAR SPREAD LENS 42



19810 0030 SPREAD LENS 42

DELTALIGHT

SPLITBOX 2 SPY 52 TW 93045

100072 9030 B




13

19810 0040

SOFTENING LENS 42

☐




13

19810 0050

GLASS SBL 42

☐




14

19810 0060 B

HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



40

19810 0100 B

SPY 52 TUBE B

☐

19810 0100 FBR

SPY 52 TUBE FBR

☐

19810 0100 FG

SPY 52 TUBE FG

☐

19810 0100 GC

SPY 52 TUBE GC

☐

19810 0100 W

SPY 52 TUBE W

☐

Replaceable reflector / lens



18

19810 0180

SPY 52 REFLECTOR 20°

☐



18

19810 0190

SPY 52 REFLECTOR 45°

☐

DELTALIGHT

SPLITBOX 2 SPY 52 TW 93045

100072 9030 B



19810 0240 SPY 52 REFLECTOR 30°



Notes: