



OML50 - PRISMATIC LENS DU HE 656mm 940

31639 9400 B

BESCHIKBAAR IN
ZWART 31639 9400 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1
INFO	INCL. LED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 9,7W / CRI>90 (R9: 50) / 4000K / 1663lm UP: LED cluster 8,2W / CRI>90 (R9: 50) / 4000K / 1322lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 1663lm // 9,7W // 171lm/W UP: 1322lm // 8,2W // 162lm/W

Notes: