



## DEEP RINGO HE 92720

19440 9220 BRBB

AVAILABLE IN

**NOIR** 19440 9220 B

**ALU BROSSÉ** 19440 9220 BRA

**ANTHRACITE BROSSÉ** 19440 9220 BRAT

**BRONZE BRUN BROSSÉ** 19440 9220 BRBB

**CUIVRE BROSSÉ** 19440 9220 BRCU

**OR BROSSÉ** 19440 9220 BRG

**BRONZE VIEUX BROSSÉ** 19440 9220 BROB

**CRÈME** 19440 9220 CR

**FLEMISH BRONZE** 19440 9220 FBR

**FLEMISH GOLD** 19440 9220 FG

**COULEUR OR** 19440 9220 GC

**NOIR PIANO** 19440 9220 PB

**BLANC** 19440 9220 W



[View on website](#)



### General info

|                                           |                                               |
|-------------------------------------------|-----------------------------------------------|
| <b>LOCATION</b>                           | interieur                                     |
| <b>INSTALLATION</b>                       | Plafond Encastré                              |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | circulaire - 76                               |
| <b>RECESSED DEPTH (MM)</b>                | 90                                            |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | min.5                                         |
| <b>INGRESS PROTECTION</b>                 | IP43/20                                       |
| <b>WEIGHT (KG)</b>                        | 0.2                                           |
| <b>ADJUSTABILITY</b>                      | non réglable                                  |
| <b>INFORMATION</b>                        | LENS FL-20°<br>EXCL.LED POWER SUPPLY 350mA-DC |

### Electrical info

|                      |                                      |
|----------------------|--------------------------------------|
| <b>CLASS</b>         | III                                  |
| <b>DIM TYPE</b>      | selon le type d'alimentation externe |
| <b>ENERGY CLASS</b>  | D                                    |
| <b>CERTIFICATION</b> | EPD, LCA                             |

### Lightsource info

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                            |
| <b>LIGHTSOURCE</b>                 | LED array 6W / CRI>90 (R9: 50) / 2700K / 905lm |
| <b>RVALUES</b>                     | rf: 96 / Rg: 99                                |
| <b>SDMC</b>                        | SDCM2                                          |
| <b>RISKGROUP</b>                   | RG1                                            |
| <b>LM80</b>                        | L90B10 > 50000                                 |
| <b>BEAMANGLE</b>                   | 20°                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 905lm // 6W // 150lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 774lm // 6,9W // 112lm/W                       |

### Remarks

High Efficacy : > 100lm/W

### Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [19440\\_XXX0\\_HAND.pdf](#)

CEILING COMPATIBILITY

| Ceiling Type                                                                                                  | Mounting Kit |
|---------------------------------------------------------------------------------------------------------------|--------------|
|  System ceiling               | -            |
|  Plasterboard                 | -            |
|  Stucanet                     | -            |
|  Wood                         | -            |
|  Concrete                    | -            |
|  Concrete + plaster         | -            |
|  Lintel + plaster           | -            |
|  Hollow-core slab           | -            |
|  Hollow-core slab + plaster | -            |
|  Stretched ceiling          | -            |

FINISH YOUR SPECIFICATION

les batteries de secours







|                                                                                    |                                                                     |                          |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------|--------------------------|
|  | <b>21032 0270 B</b> EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B | <input type="checkbox"/> |
|                                                                                    | <b>21032 0270 W</b> EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W | <input type="checkbox"/> |

DEEP RINGO HE 92720

19440 9220 BRBB

les alimentations led

# of Fixtures

| web2print_power_supply_info_box                                                    |                                                                                                                     |         | Min current   Max current |
|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|---------|---------------------------|
|    | <b>300 90 91</b><br>LED POWER SUPPLY 350mA-DC / 15W<br><br>Dimtype: non dimmable<br>Cutout dimension (mm): 40       | 2(1)    | <input type="checkbox"/>  |
|    | <b>300 90 110</b><br>LED POWER SUPPLY 350mA-DC / 10W DIM8<br><br>Dimtype: fin de phase<br>Cutout dimension (mm): 42 | 1       | <input type="checkbox"/>  |
|    | <b>300 90 116</b><br>LED POWER SUPPLY 350mA-DC / 18W DIM8<br><br>Dimtype: fin de phase<br>Cutout dimension (mm): 55 | 2->2    | <input type="checkbox"/>  |
|  | <b>21012 0515</b><br>LED POWER SUPPLY MULTI POWER DIM5<br><br>Dimtype: DALI<br>Cutout dimension (mm): 55            | 1(1)    | <input type="checkbox"/>  |
|  | <b>21012 0520</b><br>LED POWER SUPPLY 350mA-DC / 8W<br><br>Dimtype: non dimmable<br>Cutout dimension (mm): 47       | 1(0)    | <input type="checkbox"/>  |
|  | <b>21012 0575</b><br>LED POWER SUPPLY MULTI POWER DIM5<br><br>Dimtype: DALI<br>Cutout dimension (mm): 55            | 2->3(2) | <input type="checkbox"/>  |

Notes: