



STIP W R 930

223 54 93 N

AVAILABLE IN



ALU GREY 223 54 93 A

BLACK 223 54 93 B

FLEMISH BRONZE OUTDOOR 223 54 93 FBRX

ANTHRACITE 223 54 93 N

WHITE 223 54 93 W



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
TM-30 VALUES	rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
LED TECHNICS (LIGHT SOURCE)	385lm // 3,9W // 98lm/W
LED TECHNICS (LUMINAIRE)	265lm // 4,5W // 59lm/W

For detailed installation instructions, please consult the manual : [223_54_83_HAND.pdf](#)

Notes:

DELTALIGHT

STIP W R 930

223 54 93 N