



## LOGIC LINEAR ON 880 92715 DIM5

30835 9215 B

AVAILABLE IN



**ALU GREY** 30835 9215 A

**BLACK** 30835 9215 B

**FLEMISH BRONZE OUTDOOR** 30835 9215 FBRX

**ANTHRACITE** 30835 9215 N

**WHITE** 30835 9215 W



[View on website](#)



| General info                         |                                                                      |
|--------------------------------------|----------------------------------------------------------------------|
| LOCATION                             | outdoor                                                              |
| INSTALLATION                         | Floor Surface mounted, Wall Surface mounted                          |
| INGRESS PROTECTION                   | IP67                                                                 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07                                                                 |
| WEIGHT (KG)                          | 2                                                                    |
| INFORMATION                          | 16 x LENS SP-15°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

| Electrical info |          |
|-----------------|----------|
| ELECTRICAL      | 48V-DC   |
| CLASS           | III      |
| DIM TYPE        | DALI     |
| ENERGY CLASS    | F        |
| CERTIFICATES    | CB, ENEC |

| Lightsource info            |                                                      |
|-----------------------------|------------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                                  |
| LIGHTSOURCE                 | LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm |
| TM-30 VALUES                | Rf: 91 / Rg: 100                                     |
| SDCM                        | SDCM3                                                |
| RISKGROUP                   | RG2                                                  |
| LM80                        | L80 > 150000                                         |
| BEAMANGLE                   | 15°                                                  |
| LED TECHNICS (LIGHT SOURCE) | 3288lm // 28,8W // 111lm/W                           |
| LED TECHNICS (LUMINAIRE)    | 2880lm // 33,1W // 87lm/W                            |

| Requirements              |  |
|---------------------------|--|
| WALL BRACKET SET          |  |
| FLOOR BRACKET SET         |  |
| IP68 CABLE + CONNECTOR 5P |  |
| LED POWER SUPPLY 48V-DC   |  |

| Options                 |  |
|-------------------------|--|
| THROUGH WIRING SET IP68 |  |

## LOGIC LINEAR ON 880 92715 DIM5

30835 9215 B

For detailed installation instructions, please consult the manual : [30835\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0390** LED POWER SUPPLY 48V-DC / 90W

Dimtype: non-dimmable

Cutout dimension (mm): 75

2

#### Fixation components



**30810 0040**

LOGIC LINEAR 880 BOX EXTEND

**30810 0040 INOX** WALL BRACKET SET 60 INOX

**30810 0040 N**

WALL BRACKET SET 60 N




**30810 0050 INOX**

WALL BRACKET SET 100 INOX

**30810 0050 N**

WALL BRACKET SET 100 N



**30810 0060 INOX**

WALL BRACKET SET 200 INOX

**30810 0060 N**

WALL BRACKET SET 200 N

# DELTALIGHT

## LOGIC LINEAR ON 880 92715 DIM5

30835 9215 B



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0110** THROUGH WIRING SET IP68 880

☐

Notes: