



SUPERLOOP SLIM



The Superloop Slim family is an extensive range of slim circular luminaires with options of inner, outer or down illumination.

Specification	
Installation Method:	4" junction box
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI	90
SDCM:	3
LED Maintenance:	L70>30,000h

*Power	07	09	12	17
Medium Power (MP):	25W	33W	42W	59W
² Remote Power Supply Capacity (# luminaires):	D1-UNV min1-max1			
High Power (HP):	34W	45W	58W	82W
² Remote Power Supply Capacity (# luminaires):	D1-UNV min1-max1			

Delivered Lumens	2700K			3000K		
**Light Direction:	In	Out	Down	In	Out	Down
Superloop 07:	1713	1713	1713	1713	1713	1713
Superloop 09:	2285	2285		2285	2285	
Superloop 12:	2951	2951	2951	2951	2951	2951
Superloop 17:				4188	4188	

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: SLPR09O-30SBLHP-FG-B-HCPRRMTD1-UNV

Luminaire	Shape	Size	Light Direction**	CCT	Optic	Power*	Finish	Hardware Finish*	Type	Installation	Application	Controls***
SLP SUPERLOOP	R Round	07 694mm / 27 ⁵ / ₁₆ "	D Down I In O Out	27 2700K 30 3000K	SBL Sandblasted lens	MP Medium Power HP High Power	B Black FBR Flemish Bronze FG Flemish Gold GC Gold Colored W White	B Black W White	HC Horizontal, 9' cables,3 suspension points	NA Includes surface canopy	PB Power Box canopy	D1-UNV 0-10V dim 120-277V D1-347 0-10V dim 347V D8-120 ³ FE ELV dim 120V
		09 925mm 36 ¹³ / ₁₂ "	I In O Out									
		12 1191mm / 46 ⁷ / ₈ "	D Down I In O Out							PR Round coverplate for 4" junction box PS Square coverplate for 4" junction box	RMT ² Remote Power Supply	D1-UNV 0-10V dim 120-277V D1-347 0-10V dim 347V
		17 1688 mm / 66 ¹⁵ / ₃₂ "	I In O Out	30 3000K								

¹ Applies to PS & PR (coverplate) or PB (power box).

² Remote power supply capacity noted in table above.

³ Only available for sizes with Power under 40W max.

*** Contact factory for Dali, DMX, or other dimming options.

Related Products

Superloop, Superloop MDL (48V track), Supernova, Super-Oh

DELTALIGHT


www.deltalight.com






Finish Options

SUPERLOOP SLIM IN 07



BLACK

SUPERLOOP SLIM IN 09




FLEMISH BRONZE



FLEMISH GOLD

SUPERLOOP SLIM IN 12




GOLD COLORED




WHITE

SUPERLOOP SLIM IN 17





SUPERLOOP SLIM OUT 07



BLACK

SUPERLOOP SLIM OUT 09




FLEMISH BRONZE



FLEMISH GOLD

SUPERLOOP SLIM OUT 12



GOLD COLORED




WHITE

SUPERLOOP SLIM OUT 17




SUPERLOOP SLIM DOWN 07



BLACK

SUPERLOOP SLIM DOWN 12




GOLD COLORED



WHITE

Photometric Data

SUPERLOOP SLIM SBL



SANDBLASTED LENS

DELTALIGHT

www.deltalight.com

SUPERLOOP SLIM Ver 10 10.15.25

2




Installation Options

REMOTE DRIVER (With Controls D8)

A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm


- For Remote application
- ETL Listed
- Damp rated



REMOTE DRIVER (With Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
A: 203mm x B: 72mm x C: 108mm


- For Remote application
- ETL Listed
- Damp rated




PR - COVERPLATE R 104

PS - COVERPLATE S 103


PB - POWER BOX




BLACK or WHITE
Requires 4" junction box



BLACK or WHITE
Requires 4" junction box



POWER BOX H
Powerbox H used with
Size 9 Power HP, Size 12,17



POWER BOX L
Powerbox L used with
Size 7, 9 with Power MP



BLACK



WHITE

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D1 (With Size 17)

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥90
- THD @ Full Load <20%

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DDTV-XX

D8 (With Size 07 MP/HP & Size 09 MP)

- Dimming Control Phase Control
- Dimming Range 20-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80
- THD @ Full Load <10%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.