



BOXY XL S 92720 DIM5



10723 9215 W-W

AVAILABLE IN

BLACK-BLACK 10723 9215 B-B

WHITE-BLACK 10723 9215 W-B

WHITE-WHITE 10723 9215 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 60) / 2700K / 2209lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	2209lm // 16,3W // 136lm/W
LED TECHNICS (LUMINAIRE)	1929lm // 18,7W // 103lm/W


Accessories

HONEYCOMB 78
SOFTENING LENS 78
GLASS SBL 78

For detailed installation instructions, please consult the manual : [10723_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



Ø78

201 02 01 B HONEYCOMB 78 B

☐

Ø78

201 02 04 SOFTENING LENS 78

☐

Ø78

201 02 05 GLASS SBL 78

☐

Notes: