

EXCLUSIVELY AVAILABLE IN INDIA



COMPO L WALLWASH TW 940

9 15742 9000 C

AVAILABLE IN

CHROME 9 15742 9000 C

BLANC 9 15742 9000 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.466
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 1800K-4000K / 1832lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	1832lm // 17,8W // 101lm/W
LED TECHNICS (LUMINAIRE)	579lm // 20,5W // 28lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

For detailed installation instructions, please consult the manual : [9_15742_XXX0_HAND.pdf](#)

COMPO L WALLWASH TW 940

9 15742 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 6000 LED POWER SUPPLY MULTIPOWER 20W DALI DT8 500mA	1

kit de montage	
 15710 0030 B MOUNTING KIT COMPO L TRIM B	☐
Cutout dimension (mm): 92	
15710 0030 W MOUNTING KIT COMPO L TRIM W	☐
 15710 0060 MOUNTING KIT COMPO L TRIMLESS	☐
Cutout dimension (mm): 92	

Notes: