





INFORM SQ P200-7 DOWN 92767

REFERENCE 25517 9220 B-B

AVAILABLE IN
BLACK-BLACK 25517 9220 B-B
BLACK-FLEMISH GOLD 25517 9220 B-FG
WHITE-BLACK 25517 9220 W-B
WHITE-WHITE 25517 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	84 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 700/1050mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 24,6-39,1W / CRI>90 (R9: 50) / 2700K / 3545-5124lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	5124lm // 39,1W // 131lm/W
LED TECHNICS (LUMINAIRE)	4473lm // 45W // 99lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)
 INFORM POWER SUPPLY 45W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : [25517_XXX0_HAND.pdf](#)

INFORM SQ P200-7 DOWN 92767

25517 9220 B-B

FINISH YOUR SPECIFICATION


Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




25510 0010 B INFORM SQ POWERBOX 50W B

1

Dimtype: non-dimmable

25510 0010 W INFORM SQ POWERBOX 50W W

1



25510 0015 B INFORM SQ POWERBOX 50W DIM5 B

1

Dimtype: DALI

25510 0015 W INFORM SQ POWERBOX 50W DIM5 W

1


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0385 INFORM POWER SUPPLY 45W DIM5

1

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W

1

Dimtype: non-dimmable

Electric connection parts

of Fixtures




of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

INFORM SQ P200-7 DOWN 92767

25517 9220 B-B



15225 0350 B SUSPENSION + CONNECTION ST B

2 needed

☐

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W

2 needed

☐

Notes: