

SPM20 - SPY 392 AIR SOFT 93020

REFERENCE

29816 9020 W

AVAILABLE IN



BLACK 29816 9020 B

FLEMISH BRONZE 29816 9020 FBR

FLEMISH GOLD 29816 9020 FG

GOLD COLOURED 29816 9020 GC

WHITE 29816 9020 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1246lm // 12W // 105lm/W
LED TECHNICS (LUMINAIRE)	1016lm // 13,8W // 74lm/W


Requirements

SPM20 - AIR KIT 1

SPY 39 TUBE

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [29816_XXX0_HAND.pdf](#)




Cutout dimension (mm): 27

7

7

Min current | Max current




Dimtype: 1-10V

Cutout dimension (mm): 30

-

7




Dimtype: DALI

Cutout dimension (mm): 45

—

7




Dimtype: non-dimmable

Cutout dimension (mm): 30

-

7




Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

—

7




Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56

—

7



Dimtype: 1-10V or DALI or push button











Cutout dimension (mm): 82

2(2)

7





SPM20 - SPY 392 AIR SOFT 93020

29816 9020 W

	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	3(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1)	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	2(2)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1	☐

SPM20 - SPY 392 AIR SOFT 93020

29816 9020 W

	<div><div><u>21012 0268</u></div><div>LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8</div></div>	1	☐
<div>Dimtype: mains (phase cut-off)</div> <div>Cutout dimension (mm): 50</div>			
	<div><div><u>21012 0298</u></div><div>LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8</div></div>	1	☐
<div>Dimtype: mains (phase cut-off)</div> <div>Cutout dimension (mm): 48</div>			
	<div><div><u>21012 0308</u></div><div>LED POWER SUPPLY 350mA / 7,35W DIM8</div></div>	1/2	☐
<div>Dimtype: mains (phase cut-off)</div> <div>Cutout dimension (mm): 40</div>			
	<div><div><u>21032 0295</u></div><div>LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5</div></div>	1	☐
<div>Dimtype: DALI</div> <div>Cutout dimension (mm): 30</div>			

Notes: