



M26L - SPY 391 93020 MDL

23258 9320 W

AVAILABLE IN

NEGRO 23258 9320 B

ALU CEPILLADO 23258 9320 BRA

ANTRACITA CEPILLADO 23258 9320 BRAT

COBRE CEPILLADO 23258 9320 BRCU

ORO CEPILLADO 23258 9320 BRG

BRONCE VIEJO CEPILLADO 23258 9320 BROB

FLEMISH BRONZE 23258 9320 FBR

FLEMISH GOLD 23258 9320 FG

ORO COLOREADO 23258 9320 GC

NEGRO PIANO 23258 9320 PB

BLANCO 23258 9320 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Sistemas de baja tensión Montado en sistemas de baja tensión
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° giratorio, 360° orientable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1 a 10 v o DALI o SWITCH DE PRESION
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	888lm // 9,9W // 90lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23258_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Cable de alimentación

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = Regulable inalámbrico

SMART 48

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1 a 10 V o DALI o switch de presion



300 90 012 SMART 48 MODULATOR WD

19

Dimtype: WDL = Regulable inalámbrico

Fuente de Alimentación LED

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: no dimerizable

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 W

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	24	☐
Dimtype: no dimerizable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	10	☐
Dimtype: no dimerizable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	20	☐
Dimtype: no dimerizable			
Cutout dimension (mm): 40			

Dispositivos de modificación de Luz

	24144 0030 B VISOR 39 B	☐
---	--------------------------------	--------------------------

Termina tu producto









	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FC SPY 39 TUBE FC	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 W


COMPATIBLE COMPOSABLES

SHIFTLINE M26L FLOOR		Available Colours
	29321 0010 SLM26L F MDL	
	29322 002W SLM26L F MDL WD	
SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         
SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	

DELTALIGHT

M26L - SPY 391 93020 MDL

23258 9320 W



23375 0030 SLM35R - PROFILE 3m



Notes: