





## D-LINER 30 INF LOC1 1390 93058 RD


32055 9320 B-B

AVAILABLE IN

**BLACK-BLACK** 32055 9320 B-B

**WHITE-WHITE** 32055 9320 W-W



 [View on website](#)



### General info

|                           |   |
|---------------------------|---|
| <b>LOCATION</b>           | indoor  |
| <b>INSTALLATION</b>       | Ceiling Recessed  |
| <b>INGRESS PROTECTION</b> | IP20  |
| <b>WEIGHT (KG)</b>        | 0   |
| <b>ADJUSTABILITY</b>      | non adjustable  |
| <b>INFORMATION</b>        | 60 x REFLECTOR 58°<br>EXCL.LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE 2 x 0,75mm <sup>2</sup> - 0,5m + WIELAND PLUG GST08i2 male green |

### Electrical info

|                     |     |
|---------------------|-----|
| <b>CLASS</b>        | III |
| <b>ENERGY CLASS</b> | C   |

### Lightsource info

|                                    |   |
|------------------------------------|---|
| <b>LIGHTSOURCE NAME</b>            | LED   |
| <b>LIGHTSOURCE</b>                 | LED cluster 21,6W / CRI>90 / 3000K / 3822lm |
| <b>BEAMANGLE</b>                   | 58°   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 3822lm // 21,6W // 177lm/W                  |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 3023lm // 24,8W // 122lm/W                  |

### Requirements

LED POWER SUPPLY SET LOC PARALLEL

### Options

CONNECTING CABLE LOC PARALLEL

For detailed installation instructions, please consult the manual : [32055\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## D-LINER 30 INF LOC1 1390 93058 RD

32055 9320 B-B

### CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interlu SAPP

### FINISH YOUR SPECIFICATION


#### Emergency units

# of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**32010 0195** EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

#### Current supply



**32010 1200** T CONNECTOR LOC PARALLEL



**32010 1310** CONNECTING CABLE LOC PARALLEL 1m



**32010 1320** CONNECTING CABLE LOC PARALLEL 2m



**32010 1330** CONNECTING CABLE LOC PARALLEL 3m



**32010 1340** CONNECTING CABLE LOC PARALLEL 4m

# DELTALIGHT

## D-LINER 30 INF LOC1 1390 93058 RD

32055 9320 B-B



**32010 1350** CONNECTING CABLE LOC PARALLEL 5m

### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**32010 0115** LED POWER SUPPLY SET LOC PARALLEL 650mA / 35W DIM5

1


Dimtype: DALI



**32010 0165** LED POWER SUPPLY SET LOC PARALLEL 1300mA / 100W DIM5

2->2

Dimtype: DALI



**32010 0455** LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5

3->3

Dimtype: DALI

Notes: