





M20/M26H - SPY 52 TW 96520
DIM5

23331 9025 B

AVAILABLE IN
BLACK 23331 9025 B
WHITE 23331 9025 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 30° & 45° available
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	681lm // 10,4W // 66lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42



DELTALIGHT

M20/M26H - SPY 52 TW 96520 DIM5

23331 9025 B

For detailed installation instructions, please consult the manual : [23331_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	9	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	23	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	9	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	19	
Light altering devices		
 19810 0010 B HONEYCOMB 42 SINGLE USE B		
 19810 0020 LINEAR SPREAD LENS 42		

DELTALIGHT

M20/M26H - SPY 52 TW 96520 DIM5


23331 9025 B

	19810 0030	SPREAD LENS 42	☐
	19810 0040	SOFTENING LENS 42	☐
	19810 0050	GLASS SBL 42	☐
	19810 0060 B	HONEYCOMB 42 DOUBLE USE B	☐

Finish your product

	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	19810 0180	SPY 52 REFLECTOR 20°	☐
--	-------------------	----------------------	--------------------------

DELTALIGHT

M20/M26H - SPY 52 TW 96520 DIM5

23331 9025 B



19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°



COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	30411 9205 SHIFTLINE M26H + SBL 2m DIM5	 
	30411 9305 SHIFTLINE M26H + SBL 2m DIM5	 
	30412 9205 SHIFTLINE M26H + SBL 3m DIM5	 
	30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
	30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
	30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 


DELTA LIGHT

M20/M26H - SPY 52 TW 96520 DIM5


23331 9025 B

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m





420 20 20 00 SPM20 - PROFILE 2m



DELTALIGHT

M20/M26H - SPY 52 TW 96520 DIM5

23331 9025 B

	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: