DELTALIGHT



SPYCO 70 93036 ADM DIM5

REFERENCE 19920 9335 B

AVAILABLE IN
BLACK 19920 9335 B
FULL WHITE 19920 9335 FW





View on website

General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 450/500mA-DC Max. 450mA with HONEYCOMB

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 500mA: LED array 17,2W / CRI>90 (R9: 52) / 3000K / 2101lm Or @ 450mA (+HONEYCOMB): LED array 15,3W / CRI>90 (R9: 52) / 3000K / 1913lm
TM-30 VALUES	@ 450mA (+HONEYCOMB): Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	@ 500mA: 2101lm // 17,2W // 123lm/W Or @ 450mA (+HONEYCOMB): 1913lm // 15,3W // 125lm/W
LED TECHNICS (LUMINAIRE)	@ 500mA: 1642lm // 20W // 83lm/W Or @ 450mA (+HONEYCOMB): 991lm // 18W // 56lm/W

Requirements

TRACK 3F ON

Accessories

SPYCO 70 HONEYCOMB

DELTALIGHT

SPYCO 70 93036 ADM DIM5

19920 9335 B

For detailed installation instructions, please consult the manual : **19920_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices

19922 0010 B SPYCO 70 HONEYCOMB B

COMPATIBLE TRACKS

TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	

Notes: