





DOT.COM L WALLWASH 02 ST 930 HO

424 242 02 93 W-B

AVAILABLE IN

WHITE-BLACK 424 242 02 93 W-B



[View on website](#)





General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 220 x 40
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.10
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,6W / CRI>90 (R9: 68) / 3000K / 1068lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	1068lm // 9,6W // 111lm/W
LED TECHNICS (LUMINAIRE)	581lm // 11W // 53lm/W
Requirements	
LED POWER SUPPLY 350mA-DC DIM	

For detailed installation instructions, please consult the manual : [424_242_02_XX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-











FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1-10V Cutout dimension (mm): 30	1
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	1

DELTALIGHT











DOT.COM L WALLWASH 02 ST 930 HO

424 242 02 93 W-B

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	1	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	1	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	1	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	2(2)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	3(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1)	☐

DOT.COM L WALLWASH 02 ST 930 HO

424 242 02 93 W-B

	300 90 135 LED POWER SUPPLY MULTI-POWER HV	2->3	☐
Dimtype: non-dimmable Cutout dimension (mm): 90			
	21012 0010 LED POWER SUPPLY MULTI POWER	1	☐
Dimtype: non-dimmable Cutout dimension (mm): 50			
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1	☐
Dimtype: 1-10V Cutout dimension (mm): 54			
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1	☐
Dimtype: DALI Cutout dimension (mm): 54			
	21012 004W LED POWER SUPPLY MULTI-POWER WDL	2(2)	☐
Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84			
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1	☐
Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54			
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
Dimtype: mains (phase cut-off) Cutout dimension (mm): 50			
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	1	☐
Dimtype: mains (phase cut-off) Cutout dimension (mm): 50			
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1	☐
Dimtype: mains (phase cut-off) Cutout dimension (mm): 48			
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
Dimtype: DALI Cutout dimension (mm): 30			

DELTALIGHT

DOT.COM L WALLWASH 02 ST 930 HO

424 242 02 93 W-B

Notes: