DELTALIGHT



ENTERO RD-S TRIMLESS HE 93020

REFERENCE 28486 9320 B

AVAILABLE IN
BLACK 28486 9320 B
FULL WHITE 28486 9320 FW
GOLD COLOURED 28486 9320 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	105
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.25
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	827lm // 7W // 120lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

MOUNTING KIT ENTERO ROUND S
MOUNTING KIT AIR 105
LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : **28486_XXX0_HAND.pdf**

ENTERO RD-S TRIMLESS HE 93020

28486 9320 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Plasterboard**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Stucanet**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Concrete + plaster**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Lintel + plaster**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Hollow-core slab + plaster**	28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
 **Stretched ceiling**	28400 0130 - MOUNTING KIT ENTERO RD-S WSC	Required
	28400 0070 - MOUNTING KIT ENTERO RD-S CSC	Required
 **Ventilation in plasterboard**	29810 0120 - MOUNTING KIT NO AIR 105	Required
	29810 0110 - MOUNTING KIT SIDE AIR 105	Required
	29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
 **Ventilation in concrete + plaster**	29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
	29810 0130 - MOUNTING KIT TOP AIR 105	Required
	29810 0120 - MOUNTING KIT NO AIR 105	Required

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT

ENTERO RD-S TRIMLESS HE 93020

28486 9320 B

LED power supplies

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 2(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 — 1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 — 2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 — 1(1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0520 LED POWER SUPPLY 350mA-DC / 8W — 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 47



21012 0575 LED POWER SUPPLY MULTI POWER DIM5 — 2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

Mounting kits



28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

Cutout dimension (mm): 105



28500 0220 MOUNTING KIT DEEP ENTERO RD-S TRIMLESS

Cutout dimension (mm): 133

ENTERO RD-S TRIMLESS HE 93020

28486 9320 B

Mounting kits stretched ceiling



28400 0070 MOUNTING KIT ENTERO RD-S CSC



28400 0130 MOUNTING KIT ENTERO RD-S WSC

Mounting kits side air + light



29810 0110 MOUNTING KIT SIDE AIR 105

Cutout dimension (mm): 168

Mounting kits top air + light



29810 0130 MOUNTING KIT TOP AIR 105

Cutout dimension (mm): 135

Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168

Mounting kits top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135

DELTALIGHT

ENTERO RD-S TRIMLESS HE 93020

28486 9320 B

Mounting kits no air



29810 0120 MOUNTING KIT NO AIR 105

Cutout dimension (mm): 168

Notes: