



OML50 - PRISMATIC LENS D HO 2296mm 940

31616 9400 B

AVAILABLE IN
BLACK 31616 9400 B



[View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 2.4 |
| INFORMATION | INCL.LED POWER SUPPLY CABLING 1 CIRCUIT |

Electrical info

| | |
|---------------------|----------------------|
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | non-dimmable |
| ENERGY CLASS | D |
| CERTIFICATES | EPD, RCM |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 54,3W / CRI>90 (R9: 50) / 4000K / 8487lm |
| TM-30 VALUES | Rf: 90 / Rg: 101 |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | 8487lm // 54,3W // 160lm/W |

Notes: