



OML50 - PRISMATIC LENS DU HE
984mm 930 DIM5

31640 9305 B

AVAILABLE IN
BLACK 31640 9305 B

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 14,6W / CRI>90 (R9: 50) / 3000K / 2394lm UP: LED cluster 12,2W / CRI>90 (R9: 50) / 3000K / 1901lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2394lm // 14,6W // 164lm/W UP: 1901lm // 12,2W // 155lm/W
Options	
WIRELESS CONTROL DIM5	

Notes: