





SUPERDOME 9528 RECESSED DIM5

321 96 9528 ED5 W-W

AVAILABLE IN

BLACK-WHITE 321 96 9528 ED5 B-W

WHITE-WHITE 321 96 9528 ED5 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	350
INGRESS PROTECTION	IP20
WEIGHT (KG)	17
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL FIX ANGLE 10° INCL.2 x LED POWER SUPPLY 350mA

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 105W / CRI>90 / 3000K / 16950lm
LED TECHNICS (LIGHT SOURCE)	16950lm // 105W // 161lm/W
LED TECHNICS (LUMINAIRE)	13043lm // 120,8W // 108lm/W

Requirements

SUPERDOME RECESSED KIT

For detailed installation instructions, please consult the manual : [321_96_9528_ED5_HAND.pdf](#)

SUPERDOME 9528 RECESSED DIM5

321 96 9528 ED5 W-W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	Plasterboard  321 96 1036 - SUPERDOME RECESSED KIT Required
	Stucanet  321 96 1036 - SUPERDOME RECESSED KIT Required

FINISH YOUR SPECIFICATION

Recessed kits



321 96 1036 SUPERDOME RECESSED KIT

Cutout dimension (mm): 1105 x 1105



Notes: