



OML50 - PRISMATIC LENS D HO  
2296mm 940 DIM5

31616 9405 B

BESCHIKBAAR IN  
ZWART 31616 9405 B

 [Bekijk op website](#)



|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| Algemene info            |                                                                          |
| LOCATIE                  | binnen                                                                   |
| STOF EN WATERDICHTHEID   | IP20                                                                     |
| GEWICHT (KG)             | 2.4                                                                      |
| INFO                     | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |
| Elektrische info         |                                                                          |
| ELEKTRISCH               | 220-240V / 0 50-60Hz                                                     |
| KLASSE                   | I                                                                        |
| VOEDING INBEGREPEN       | YES                                                                      |
| DIM TYPE                 | DALI                                                                     |
| ENERGIE KLASSE           | D                                                                        |
| CERTIFICATES             | EPD, RCM                                                                 |
| Info lichtbron           |                                                                          |
| LIGHTSOURCE NAME         | LED                                                                      |
| LICHTBRON                | LED cluster 54,3W / CRI>90 (R9: 50) / 4000K / 8487lm                     |
| TM-30 WAARDEN            | Rf: 90 / Rg: 101                                                         |
| SMDC                     | SDCM3                                                                    |
| RISK-GROEP               | RG1                                                                      |
| LM80                     | L80 > 60000                                                              |
| LED TECHNIEK (LICHTBRON) | 8487lm // 54,3W // 160lm/W                                               |
| Opties                   |                                                                          |
| WIRELESS CONTROL DIM5    |                                                                          |

Notes: