





PUNK 621 C 93033 DIM8

471 321 811 932 ED8 BP

AVAILABLE IN
BLACK 471 321 811 932 ED8 B
BLACK PURE 471 321 811 932 ED8 BP
GOLD COLOURED 471 321 811 932 ED8 GC



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	404lm // 6,7W // 61lm/W

Requirements	
SPY TUBE	

Options	
SUSPENSION + CONNECTION TRIMLESS	
COVERSET R 90-100	

Accessories	
HONEYCOMB 50	
LINEAR SPREAD LENS 50	
SPREAD LENS 50	
SOFTENING LENS 50	

DELTALIGHT

PUNK 621 C 93033 DIM8


471 321 811 932 ED8 BP

GLASS SBL 50



For detailed installation instructions, please consult the manual : [471_321_811_XXX_ED8_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Miscellaneous control equipment

	300 90 004 ED8 WIRELESS CONTROL DIM8	☐
Dimtype: WDL = wireless dimmable		
Cutout dimension (mm): 40		

Coversets

	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐
	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

Suspension parts





	328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		

DELTALIGHT

PUNK 621 C 93033 DIM8

471 321 811 932 ED8 BP

Light altering devices

 Ø50	413 03 01 B HONEYCOMB 50 B	☐
 Ø50	413 03 02 LINEAR SPREAD LENS 50	☐
 Ø50	413 03 03 SPREAD LENS 50	☐
 Ø50	413 03 04 SOFTENING LENS 50	☐
 Ø50	413 03 05 GLASS SBL 50	☐

Finish your product

 53 Ø60	414 01 00 B SPY TUBE B	☐
	414 01 00 FBR SPY TUBE FBR	☐
	414 01 00 FG SPY TUBE FG	☐
	414 01 00 MMAT SPY TUBE MMAT	☐
	414 01 00 SG SPY TUBE SG	☐
	414 01 00 W SPY TUBE W	☐

DELTALIGHT

PUNK 621 C 93033 DIM8

471 321 811 932 ED8 BP

Notes: