





FRAX SB SUPERSPOT 92708 HONEYCOMB

26100 9220 N

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 26100 9220 FBRX
ANTHRACITE 26100 9220 N
PINE GREEN 26100 9220 PGR



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	3 x LENS SP-8° INCL.LED POWER SUPPLY 700mA-DC INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm ² 2m

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6W / CRI>90 (R9: 50) / 2700K / 659lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	659lm // 6W // 110lm/W
LED TECHNICS (LUMINAIRE)	540lm // 6,9W // 78lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX S KAP

DELTALIGHT


FRAX SB SUPERSPOT 92708 HONEYCOMB

26100 9220 N


For detailed installation instructions, please consult the manual : [26100_XX20_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Pins and plates for bollards

	26070 0040 FBRX FRAX PIN FBRX	☐
	26070 0040 N FRAX PIN N	☐
	26070 0040 PGR FRAX PIN PGR	☐

Fixation components

	26070 0060 FBRX FRAX BRACKET FBRX	☐
	26070 0060 N FRAX BRACKET N	☐
	26070 0060 PGR FRAX BRACKET PGR	☐

Light altering devices


	26070 0010 N FRAX S KAP N	☐
--	----------------------------------	--------------------------

DELTALIGHT


FRAX SB SUPERSPOT 92708 HONEYCOMB

26100 9220 N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26070 0050 N FRAX STRAP N

☐

Notes: