
DELTALIGHT




SPYCO ON AC 93033 DIM8

REFERENCE 19919 9328 B

AVAILABLE IN
BLACK 19919 9328 B
WHITE 19919 9328 W







View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W

Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 54) / 3000K / 630lm
TM-30 VALUES	Rf: 91 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	630lm // 8W // 79lm/W
LED TECHNICS (LUMINAIRE)	477lm // 8W // 60lm/W

Accessories

SPY TUBE S

For detailed installation instructions, please consult the manual : **19919_XXX8_HAND.pdf**


DELTALIGHT

SPYCO ON AC 93033 DIM8

19919 9328 B

FINISH YOUR SPECIFICATION

Finish your product

	**414 02 00 B**	SPY TUBE S B	☐
	414 02 00 FBR	SPY TUBE S FBR	☐
	414 02 00 FG	SPY TUBE S FG	☐
	414 02 00 MMAT	SPY TUBE S MMAT	☐
	414 02 00 SG	SPY TUBE S SG	☐
	414 02 00 W	SPY TUBE S W	☐

Notes: