





M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B

AVAILABLE IN

BLACK 421 522 811 930 MDL B

WHITE 421 522 811 930 MDL W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	1067lm // 9,9W // 108lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

BOWL GLASS CLEAR
BOWL GLASS AMBER
BOWL GLASS OPAL WHITE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B

For detailed installation instructions, please consult the manual : [421_522_811_XXX_MDL_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

16


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

8






Dimtype: non-dimmable

Cutout dimension (mm): 75

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B



	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	8	☐
Dimtype: non-dimmable			
	300 89 48 150 LED POWER SUPPLY 48V-DC / 150W	12	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	16	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

Power box

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current

	23380 001W B SLM26H - POWERBOX 48V-DC / 96W WD B	8	☐
Dimtype: WDL = wireless dimmable			
	23380 001W W SLM26H - POWERBOX 48V-DC / 96W WD W	8	☐
	23380 0010 B SLM26H - POWERBOX 48V-DC / 96W B	8	☐
Dimtype: non-dimmable			
	23380 0010 W SLM26H - POWERBOX 48V-DC / 96W W	8	☐

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B



23380 0020 B

SLM26H - MID POWERBOX 48V-DC / 96W B

8 ☐

Dimtype: non-dimmable

23380 0020 W

SLM26H - MID POWERBOX 48V-DC / 96W W

8 ☐

To be used with ...



286 67 01

BOWL GLASS CLEAR

☐



286 67 02

BOWL GLASS AMBER

☐



286 67 03


BOWL GLASS OPAL WHITE

☐

COMPATIBLE COMPOSABLES


SHIFTLINE M26H profile

Available Colours




23359 0000

SLM26H - PROFILE



23359 0010

SLM26H - PROFILE 1m




23359 0020

SLM26H - PROFILE 2m

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: