
DELTALIGHT




M20/M26H - TWEETER BL 930 MDL

REFERENCE 421 522 811 930 MDL B

AVAILABLE IN
BLACK 421 522 811 930 MDL B
WHITE 421 522 811 930 MDL W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	1067lm // 9,9W // 108lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

BOWL GLASS CLEAR
BOWL GLASS AMBER
BOWL GLASS OPAL WHITE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B

For detailed installation instructions, please consult the manual : **421_522_811_XXX_MDL_HAND.pdf**


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 16


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 16


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 90 LED POWER SUPPLY 48V-DC / 90W — 8


Dimtype: non-dimmable

Cutout dimension (mm): 75

DELTALIGHT


M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8

Dimtype: non-dimmable




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W — 12

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 20


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 16

Dimtype: non-dimmable

Cutout dimension (mm): 40

Power box	# of Fixtures
	Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



23380 001W B SLM26H - POWERBOX 48V-DC / 96W WD B — 8

Dimtype: WDL = wireless dimmable

23380 001W W SLM26H - POWERBOX 48V-DC / 96W WD W — 8



23380 0010 B SLM26H - POWERBOX 48V-DC / 96W B — 8


Dimtype: non-dimmable

23380 0010 W SLM26H - POWERBOX 48V-DC / 96W W — 8

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B




23380 0020 B SLM26H - MID POWERBOX 48V-DC / 96W B — 8


Dimtype: non-dimmable

23380 0020 W SLM26H - MID POWERBOX 48V-DC / 96W W — 8


To be used with ...



286 67 01 BOWL GLASS CLEAR




286 67 02 BOWL GLASS AMBER




286 67 03 BOWL GLASS OPAL WHITE

COMPATIBLE COMPOSABLES


SHIFTLINE M26H profile — **Available Colours**



23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m




23359 0020 SLM26H - PROFILE 2m

DELTALIGHT

M20/M26H - TWEETER BL 930 MDL

421 522 811 930 MDL B



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE





23397 0020 SPM20 ST - PROFILE 2m






23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile — Available Colours




420 20 10 00 SPM20 - PROFILE 1m






420 20 20 00 SPM20 - PROFILE 2m





420 20 30 00 SPM20 - PROFILE 3m





23301 0000 SPM20 - PROFILE B



Notes: