
DELTALIGHT




INFORM SQ P144-5 DOWN 94067

REFERENCE 25513 9420 B-B

AVAILABLE IN
BLACK-BLACK 25513 9420 B-B
BLACK-FLEMISH GOLD 25513 9420 B-FG
WHITE-BLACK 25513 9420 W-B
WHITE-WHITE 25513 9420 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 500/750mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 4000K / 2784-4026lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	4026lm // 27,9W // 144lm/W
LED TECHNICS (LUMINAIRE)	3515lm // 32,1W // 110lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)
INFORM POWER SUPPLY 45W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : **25513_XXX0_HAND.pdf**



DELTALIGHT

INFORM SQ P144-5 DOWN 94067



25513 9420 B-B

FINISH YOUR SPECIFICATION

Power box

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current
	**25510 0010 B** INFORM SQ POWERBOX 50W B **Dimtype: non-dimmable**	1 ☐
	25510 0010 W INFORM SQ POWERBOX 50W W	1 ☐
	**25510 0015 B** INFORM SQ POWERBOX 50W DIM5 B **Dimtype: DALI**	1 ☐
	25510 0015 W INFORM SQ POWERBOX 50W DIM5 W	1 ☐

LED power supplies

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current
	**25510 0385** INFORM POWER SUPPLY 45W DIM5 **Dimtype: DALI**	1 ☐
	**25510 0430** INFORM POWER SUPPLY 45W **Dimtype: non-dimmable**	1 ☐


Electric connection parts

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current

DELTALIGHT

INFORM SQ P144-5 DOWN 94067

25513 9420 B-B



15225 0350 B SUSPENSION + CONNECTION ST B — 2 needed ☐

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W — 2 needed ☐

Notes: