



M20/M26H - MULTINOVA 30 930 MDL



27947 9300 W

AVAILABLE IN

BLACK 27947 9300 B

GOLD COLOURED 27947 9300 GC

WHITE 27947 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,9W / CRI>90 (R9: 68) / 3000K / 2174lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	2174lm // 14,9W // 146lm/W
LED TECHNICS (LUMINAIRE)	1580lm // 17,1W // 92lm/W

Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27947_XXX0_HAND.pdf](#)

M20/M26H - MULTINOVA 30 930 MDL

27947 9300 W

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

11

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

11

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

11

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

6

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN



14

Dimtype: non-dimmable





DELTALIGHT

M20/M26H - MULTINOVA 30 930 MDL

27947 9300 W

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	6	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	11	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		





COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile		Available Colours
	<u>23359 0000</u> SLM26H - PROFILE	 
	<u>23359 0010</u> SLM26H - PROFILE 1m	 
	<u>23359 0020</u> SLM26H - PROFILE 2m	         
	<u>23359 0030</u> SLM26H - PROFILE 3m	         
SPLITLINE M20 ST profile		Available Colours
	<u>23397 0000</u> SPM20 ST - PROFILE	 
	<u>23397 0020</u> SPM20 ST - PROFILE 2m	 
	<u>23397 0030</u> SPM20 ST - PROFILE 3m	 

DELTALIGHT

M20/M26H - MULTINOVA 30 930 MDL

27947 9300 W

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: