


DELTALIGHT



PIN 12

229 01 12



[Auf der Website anzeigen](#)



Allgemeine Information

ANWENDUNGSBEREICH	aussenbereich
GEWICHT (KG)	0.4

Detaillierte Installationsanweisungen finden Sie in der Montageanleitung : [229_01_12_HAND.pdf](#)

WO VERWENDET

220 53 4102	WALKER 53 LED WW
220 55 4102	WALKER 55 LED WW
220 74 12	OBLIX 40
220 74 811 920	OBLIX 40 927
220 74 811 930	OBLIX 40 930
220 77 12	OBLIX 70
220 77 811 920	OBLIX 70 927
220 77 811 930	OBLIX 70 930
320 23 12	SKELP X P 40
320 26 12	SKELP X P 70
15118 9200	OBLIX 15 927
15118 9300	OBLIX 15 930
22624 9200	WALKER II 40 927
22624 9300	WALKER II 40 930
22625 9200	WALKER II 40 927
22625 9300	WALKER II 40 930
22626 9200	WALKER II 70 927
22626 9300	WALKER II 70 930
22627 9200	WALKER II 70 927
22627 9300	WALKER II 70 930
22628 9200	WALKER II 20 927
22628 9300	WALKER II 20 930
22629 9200	WALKER II 20 927
22629 9300	WALKER II 20 930
29615 9208	OONO P40 927 DIM8
29615 9308	OONO P40 930 DIM8
29616 9208	OONO P70 927 DIM8
29616 9308	OONO P70 930 DIM8

DELTALIGHT

PIN 12

229 01 12

Notes: