



ENTERO RD-M TRIMLESS TW 94018



28467 9010 GC

AVAILABLE IN

BLACK 28467 9010 B

FULL WHITE 28467 9010 FW

GOLD COLOURED 28467 9010 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	720lm // 10,4W // 70lm/W

Requirements

MOUNTING KIT ENTERO ROUND M

LED POWER SUPPLY 500mA-DC TW (Remote)

Accessories

ENTERO M HONEYCOMB

ENTERO M LINEAR SPREAD LENS

ENTERO M SPREAD LENS

ENTERO M SOFTENING LENS

ENTERO M GLASS SBL

DELTALIGHT

ENTERO RD-M TRIMLESS TW 94018

28467 9010 GC

For detailed installation instructions, please consult the manual : [28467_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required
	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

Dimtype: DALI

Cutout dimension (mm): 85

2

DELTALIGHT

ENTERO RD-M TRIMLESS TW 94018

28467 9010 GC

Mounting kits




28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.

Cutout dimension (mm): 127

7

Mounting kits stretched ceiling



28400 0080 MOUNTING KIT ENTERO RD-M CSC

7



28400 0140 MOUNTING KIT ENTERO RD-M WSC


7

Light altering devices



28500 0070 ENTERO M LINEAR SPREAD LENS

7




28500 0080 ENTERO M SPREAD LENS

7




28500 0090 ENTERO M SOFTENING LENS

7



28500 0100 ENTERO M GLASS SBL

7




28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

7

DELTALIGHT

ENTERO RD-M TRIMLESS TW 94018

28467 9010 GC



28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐



24611 0230 SPY 66 REFLECTOR 30°

☐



24611 0240 SPY 66 REFLECTOR 45°

☐

Notes: