





EN-SUITE R HE IP 92737

26322 9230 W

AVAILABLE IN
BLACK 26322 9230 B
WHITE 26322 9230 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 48
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-37° EXCL.LED POWER SUPPLY 250mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,2W / CRI>90 (R9: 50) / 2700K / 663lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	37°
LED TECHNICS (LIGHT SOURCE)	663lm // 4,2W // 157lm/W
LED TECHNICS (LUMINAIRE)	532lm // 4,8W // 110lm/W

Requirements

LED POWER SUPPLY 250mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual : [26322_XXX0_HAND.pdf](#)

DELTALIGHT

EN-SUITE R HE IP 92737

26322 9230 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

2(2)

Dimtype: DALI

Cutout dimension (mm): 72




300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2->3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2)






Dimtype: DALI

Cutout dimension (mm): 55

DELTA LIGHT

EN-SUITE R HE IP 92737

26322 9230 W

	21012 0080 LED POWER SUPPLY MULTI POWER 60-360mA-DC Dimtype: non-dimmable Cutout dimension (mm): 40	2 ☐
	21012 0095 LED POWER SUPPLY 250mA-DC / 10W DIM5 Dimtype: DALI Cutout dimension (mm): 40	2 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2 ☐
	21012 0338 LED POWER SUPPLY 250mA / 6W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	1 ☐

Notes: