

INFORM ST 1380 92767

25503 9220 B-B


AVAILABLE IN

BLACK-BLACK 25503 9220 B-B

BLACK-FLEMISH GOLD 25503 9220 B-FG

WHITE-BLACK 25503 9220 W-B

WHITE-WHITE 25503 9220 W-W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 1393
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 500/750mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 2700K / 2532-3660lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3660lm // 27,9W // 131lm/W
LED TECHNICS (LUMINAIRE)	3195lm // 32,1W // 100lm/W

Requirements

INFORM POWER SUPPLY 45W




For detailed installation instructions, please consult the manual : [25503_XXX0_HAND.pdf](#)

DELTALIGHT

INFORM ST 1380 92767

25503 9220 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



25510 0385 INFORM POWER SUPPLY 45W DIM5

1

Dimtype: DALI



25510 0430 INFORM POWER SUPPLY 45W

1

Dimtype: non-dimmable

Notes: