




MULTINOVA 55 PRISM 930 ADM
28032 9300 B

AVAILABLE IN
BLACK 28032 9300 B
WHITE 28032 9300 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC 3F MULTI POWER ADAPTER
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4767lm // 34,4W // 139lm/W
LED TECHNICS (LUMINAIRE)	3466lm // 39,6W // 88lm/W
Requirements	
TRACK 3F DIM	

For detailed installation instructions, please consult the manual : [28032_XXX0_HAND.pdf](#)

DELTALIGHT

MULTINOVA 55 PRISM 930 ADM

28032 9300 B

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	  
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	  
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	  

Notes: