



## OML50 C - LED ARRAY UP HE 1312mm 940 DIM5

31138 9405



[Bekijk op website](#)



Algemene info	
<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	0.8
<b>INFO</b>	CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
<b>ELEKTRISCH</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING INBEGREPEN</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	D
<b>CERTIFICATES</b>	EPD, RCM
Info lichtbron	
<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
<b>TM-30 WAARDEN</b>	Rf: 90 / Rg: 101
<b>SMDC</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	2643lm // 16,3W // 162lm/W
Opties	
WIRELESS CONTROL DIM5	

Notes: